



电气指标:

1. 频率范围: DC~6GHz
2. 接触电阻
 内导体: $\leq 3 \text{ m}\Omega$
 外导体: $\leq 2 \text{ m}\Omega$
3. 绝缘电阻: $\geq 5000\text{M}\Omega$
4. 介质耐压: 1000V (rms)
5. 使用寿命: 500次

Electrical Characteristics:

1. Frequency range: DC~6GHz
2. Contact resistance
 Center conductor: $\leq 3 \text{ m}\Omega$
 Out conductor: $\leq 2 \text{ m}\Omega$
3. Insulation resistance: $\geq 5000\text{M}\Omega$
4. Insulator withstanding: 1000V (rms)
5. Durability: 500cycles

执行标准: GB681 (MIL-C-39012)

Application: GB681 (MIL-C-39012)

材料&镀层

Material&Finishing

1. 中心接触件: 黄铜, 镀金
2. 外壳: 黄铜, 镀金
3. 绝缘子: PTFE

1.Center pin: **Brass, gold plated**

2. Body : **brass, gold plated**

3. Insulators: PTFE

FIRST ANGLE PROJECTION		SCALE
THIRD ANGLE PROJECTION		2:1
DRAWN	NAME	DATE
CHECKED	Mike Wang	08-01-12
APPROVED	Magi Wang	08-01-12
	Teresa Shen	08-01-12

SMA-JJA		UNITS	mm
SMA male to male adaptor		REV	
		V1.0	

UNLESS OTHERWISE SPECIFIED			
DIMENSIONS ARE	mm.	TOLERANCES ARE:	ARC:
FRACTIONS	DECIMALS	ANGLES	
.X±	.20 ±	1°	
.XX±	.10		
.XXX±			

